



Network

# QNE-C9013RL

8MP AI Dual Light Flateye Camera



## Key Features

- Max. 8MP resolution
- 3.0 mm fixed lens
- Color: 0.034Lux (F1.6, 1/30sec)  
/ BW: 0.0034Lux (F1.6, 1/30sec, 30IRE)
- Maximum 30fps@8MP (H.265/H.264)
- Light viewable length : White LED : 30m(98.42ft), IR : 30m(98.42ft)
- Day & Night (ICR), WDR (120dB), WiseNR II (Using AI engine)
- H.265, H.264, MJPEG, WiseStreamIII (Using AI engine)
- Analytics events based on AI engine (NPU) : Object detection (Person/Vehicle - car, truck, bus, bicycle, motorcycle), Motion detection, Virtual line(Crossing/Direction), Virtual area(Loitering/Intrusion/Enter/Exit)
- IP66/IP67, IK10
- PoE: Max 10W

# QNE-C9013RL

8MP AI Dual Light Flateye Camera



## Specifications

### Video

Imaging Device	Size	1/2.8"
	Type	CMOS
Resolution	2592x1944, 1280x720, 1280x1024, 720x480, 1280x960, 1024x768, 800x600, 720x576, 640x360, 640x480, 1920x1080, 2688x1520, 3328x1872, 3840x2160, 800x448, 3072x1728, 1600x1200, 320x240	
Max. Framerate	H.265/H.264	30fps/25fps(60Hz/50Hz)
	MJPEG	30fps(@8MP Max. 5fps)
Min. Illumination (Lux)	Color(1/30sec, 30IRE)	0.034
	BW(1/30sec, 30IRE)	0.0034

### Lens

Focal Length (mm)	3.0	
Max Aperture Ratio (F number)	Wide	1.6
Angular Field of View	Horizontal	108°
	Vertical	59°
	Diagonal	127°
Min. Object Distance	0.5m(1.64ft)	
Focus Control	Fixed	
Lens Type	Fixed iris	
Mount Type	M12	

### Pan / Tilt / Rotate

Pan / Tilt / Rotate Range	Pan	0°~350°
	Tilt	0°~75°
	Rotate	0°~360°

### Operational

Day & Night	Auto(ICR)
Backlight Compensation	SSDR, BLC, WDR
Wide Dynamic Range (dB)	120

## Operational

<b>Digital Noise Reduction</b>		SSNR V , WiseNR II (Based on AI engine)
<b>Motion Detection</b>	Quantity	8ea
	Shape	8point Polygonal zones
<b>Privacy Masking</b>	Quantity	32ea
	Shape	4point Quadrangle zones
	Color / Option	Red, Blue, Black, Green, White, Gray
<b>Gain Control</b>		High, Low, Middle
<b>White Balance</b>		Manual, AWC, ATW, Indoor, Outdoor
<b>LDC</b>		Support
<b>Electronic Shutter</b>	Mode	Maximum, Minimum, Anti flicker
	Speed Range	1/5~1/12,000sec
<b>Video Rotation</b>		Flip, Hallway view(90°/270°), Mirror
<b>Alarm Triggers</b>		MQTT subscription, Analytics, Network disconnect
<b>Alarm Events When Alarm Trigger Occurred</b>		Light alarm, Handover: PTZ preset, send message by HTTP/HTTPS/TCP, Notification: e-mail, MQTT: publication, Recording: SD/SDHC/SDXC or NAS recording at event triggers, File upload(image): e-mail/FTP
<b>Light Type</b>		IR LED, Warm color
<b>Light Viewable Length</b>	Warm Light	30m(98.42ft)
	IR	30m(98.42ft)
<b>IR Wavelength</b>		850nm

## Analytics

<b>Classified Object Type</b>		Vehicle, Person
<b>Attributes</b>	Vehicle	Type(car, bus, truck, motorcycle, bicycle)
<b>Thumbnail</b>		DetectionShot
<b>Analytics Events</b>	Based on AI Engine	Virtual area(Loitering/Intrusion/Enter/Exit), Virtual line(Crossing/Direction), Motion detection, Object detection
	Normal	Tampering, Virtual area(Appear/Disappear), Defocus detection
<b>Business Intelligence</b>	Based on AI Engine	Queue management, Heatmap, Vehicle counting, People counting

## Network

<b>Ethernet</b>		RJ-45(10/100BASE-T)
<b>Video Compression</b>		H.265/H.264: Main/High, MJPEG
<b>Smart Codec</b>		WiseStreamIII, Manual
<b>Bitrate Control</b>		H.265/H.264: CBR or VBR, MJPEG: VBR
<b>Streaming</b>	Unicast	Up to 20 users
	Multicast	Support
	Multiple Streaming	Up to 5 profiles

## Network

Protocol		UPnP, RTP(UDP), IPv4, HTTPS, FTP, NTP, TCP/IP, ARP, DHCP, HTTP, SRTP(TCP, UDP Unicast), CDP, LLDP, MQTT, RTSP, ICMP, RTCP, IPv6, UDP/IP, Bonjour, DNS, SNMPv1/v2c/v3(MIB-2), RTP(TCP), SSL/TLS, QoS, SMTP, DDNS, IGMP
Application Programming Interface	ONVIF	S, M, G, T
	Others	Hanwha Vision Open Platform, SUNAPI(HTTP API)
Direct Cloud Connection		Support

## Security

OS / Firmware Protect	Signed firmware, Secure boot, Encrypted firmware
User authentication	Digest authentication, Prevent brute-force attack
Network authentication	IEEE 802.1X(EAP-TLS, EAP-LEAP, EAP-PEAP, MSCHAPv2)
Secure Communication	SRTP, WSS(WebSocket Secure), HTTPS
Access Control	IP-based access control
Data Protect	Encrypt compress for live recording file export, Encryption credentials
Audit	Access / System / Event Log management
Device ID	Device certificate(Hanwha Vision Root CA)
Secure Storage	SDcard partition encrypt(AES-256)

## General

Memory	RAM	2GB
	Flash	1GB
Edge Storage	Micro SD/SDHC/SDXC	Max. 256GB x 1slot

## Environmental & Electrical

Operating Condition	Temperature	-40°C~+60°C(-40°F~+140°F)
	Humidity	0~100% RH(condensing)
	Others	Start up should be done at above -30°C, Humidity control with AIR vent
Storage Condition	Temperature	-50°C~+60°C(-58°F~+140°F)
	Humidity	0~95% RH(non-condensing)
Input Voltage		PoE(IEEE802.3af, Class3)
Power Consumption	PoE	Max. 10.0W, typical 4.5W

## Mechanical

Color	White
Material	Aluminum
RAL Code	RAL9003
Product Dimensions	ø140.0x99.6mm(ø5.51x3.92")
Product Weight	790g(1.74lb)
Compatible Gang Box	4" Octagon, Double, Single

## Certifications & Standards

EMC	RCM AS-NZS CISPR 32 Class A, VCCI CISPR 32 Class A, ICES-3(A)/NMB-3(A), FCC 47 CFR 15 Subpart B Class A, CE/UKCA - EN55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3
Safety	UL 62368-1, CAN/CSA C22.2 NO. 62368-1, IEC 62471
Environment	IEC 62262 IK10, IEC/EN 63000, IEC 60529 IP66, IEC 60529 IP67

## DORI (EN62676-4 standard)

Detect (25PPM/ 8PPF)	Wide	55.8m(183.07ft)
Observe (63PPM/ 19PPF)	Wide	22.3m(73.23ft)
Recognize (125PPM/ 38PPF)	Wide	11.2m(36.61ft)
Identify (250PPM/ 76PPF)	Wide	5.6m(18.31ft)

# QNE-C9013RL

8MP AI Dual Light Flateye Camera



**CAD**

Unit: mm [inch]

3		
2		
1	QNE-C8013RL / C9013RL	'23.09.27
No.	MODEL NAME	DATE
Unit:mm[inch]		SCALE:1/1
© Hanwha Vision		

© Hanwha Vision Co.,Ltd. All rights reserved.